

FUSIBLE ALLOY THERMAL SENSITIVE PELLET TYPE, 2 AMPERES RATED CURRENT

NEC's SEFUSE (SM/A series) is a small, solid and reliable product which can be used under 2 amperes of rated current. It protects home appliances and industrial equipment from fire by opening of electrical circuit if it senses an abnormal temperature rise.


FEATURES

- Approved by UL (USA), CSA (Canada), VDE (Germany), BEAB (UK) and MITI (Japan)
- One shot operation.
- Compact, durable and reliable by hermetic seal structure.
- Excellent sensitive to abnormal temperature rise and high accuracy in operation.
- Stable characteristics in a long-term.
- Capable of opening at cutoff current of AC 2 amperes.

APPLICATIONS

Transformers, Motors, Battery packs, Solenoid,
Electric home appliances, Electric Industrial equipments,
Office automation equipments, etc.


OUTLINE DIMENSIONS (Unit : mm)




Note: Dimensions in parentheses are for long lead devices.

The information in this document is subject to change without notice.


TYPE NAME DESIGNATION



MARKING



* Designation of Production Control No.



STANDARD RATINGS

Type Name ¹⁾	Rated Functioning Temperature	Operating Temperature	T _H T _n T _c	T _M T _m	Rated Current	Rated Voltage	Safety Standard ²⁾				
							UL	CSA	VDE	BEAB	△
SM065A0	70 °C	65±2 °C	40 °C	80 °C	2 Aac (Res.)	250 Vac (Res.)					33-528
SM072A0	76 °C	72+3/-2 °C	46 °C	100 °C			3)				
SM095A0	100 °C	95+5/-0 °C	65 °C	115 °C			E71747	LR 52330	6778.2- 4510- 1007	C0600	33-466
SM110A0	115 °C	110±2 °C	80 °C	125 °C							33-472
SM126A0	131 °C	126±2 °C	96 °C	140 °C							33-467
SM129A0	130 °C	129+0/-5 °C	96 °C	140 °C							
SM130A0	135 °C	130±2 °C	100 °C	145 °C							
SM134A0	139 °C	134±2 °C	-	-							
SM145A0	150 °C	145±2 °C	115 °C	160 °C				33-468			
SM164A0	169 °C	164+3/-2 °C	133 °C	180 °C				33-470			
SM182A0	187 °C	182±2 °C	152 °C	195 °C		33-556					

Notes : 1) The type names are for standard lead. When long lead type is required, change the last number "0" to "1".

2) The colored place means recognized safety standard.

3) Under application for C-UL

Definition of Terms

- **Rated Functioning Temperature**

Rated functioning temperature is the operating temperature of thermal cutoffs, measured using the method specified in the safety standard. In Electrical Appliance and Material Control Law of Japan, case operation should be within the specified operating temperature range of ± 7 °C. In standards that comply with the IEC standard (such as UL, CSA, VDE, BEAB), it is called the rated functioning temperature, and should operate within the prescribed temperature range of $+0/-10$ C.

It is represented by the symbol TF in the UL standard, and by the symbol Tf in the CSA, VDE and BEAB standards.

In SEFUSE, a temperature that complies with both standards is set as the rated functioning temperature, and is indicated on the body of the thermal cutoff.

- **Operating Temperature**

Operating temperature is the operating temperature range when the thermal cutoff is made to operate inside a constant temperature oven whose temperature is raised at the rate of 1 °C/min. while a detection current of 100 mA or lower is applied.

The operating temperature is a standard set by NEC and is not specified by a safety standard.

- **T_H, Th, Tc (Holding Temperature)**

Holding temperature is the maximum temperature at which, when applying a rated current to the thermal cutoff, the state of conductivity is not changed during 168 hours.

It is represented by the symbol T_H in the UL standard, Th in the CSA standard, and Tc in the VDE and BEAB standards.

- **T_M, Tm (Maximum Temperature Limit)**

Maximum temperature limit is the maximum temperature for which conductivity does not occur again after thermal cutoffs operation.

It is represented by the symbol T_M in the UL standard and by Tm in the CSA, VDE and BEAB standards.

- **Rated Current**

Maximum alternating current that can pass through the thermal cutoff and that the thermal cutoff can cut off in safety and reliability.


- **Rated Voltage**

Maximum circuit voltage that the thermal cutoff can cut off in safety and reliability.


Performance Data

SM/A Series

Temperature Rise



Response Time



Initial Characteristics

SM145A0	146 145 144	10^6 10^5 10^4	3.0 2.0 1.0	3.4 3.0 2.6
SM130A0	131 130 129	10^6 10^5 10^4	3.0 2.0 1.0	4.4 4.0 3.6
SM126A0	127 126 125	10^6 10^5 10^4	3.0 2.0 1.0	4.4 4.0 3.6
SM110A0	111 110 109	10^6 10^5 10^4	3.0 2.0 1.0	4.4 4.0 3.6
SM095A0	99 98 97	10^6 10^5 10^4	3.0 2.0 1.0	11 9 7
Part Number	Operating Temperature (°C)	Insulation Resistance after Operation (M Ω)	Withstand Voltage after Operation (kV)	Internal Resistance (m Ω /25 mm)

High Temperature Storage Test

SM145A0	@125°C	0	0	0	0	
SM130A0	@110°C	0	0	0	0	
SM126A0	@106°C	0	0	0	0	
SM110A0	@90°C	0	0	0	0	
SM095A0	@75°C	0	0	0	0	
Part Number	Change of Operating Temperature (°C)	0	10	100	1,000	10,000
		Time (Hours)				

Note: The values following @ are the storage temperature.

Cautions

This section describes cautions designed to protect the performance of the thermal cutoff. Be sure to read and fully understand these cautions.

To obtain full performance from the thermal cutoff, it is necessary for the customer to appropriately store the thermal cutoff, design appropriate circuits for the application, and perform evaluations, mounting and testing as necessary. Problems arising from the inappropriate execution of the above are the responsibility of the customer, and NEC declines any and all responsibility.

Design Cautions

- Do not use this device for any purpose other than as a thermal cutoff.
The thermal cutoff is designed to detect abnormal rises in temperature and break circuits if needed. It is not a current fuse that cuts excess current. If used as a current fuse, the SEFUSE may malfunction.
- Do not use this device in aerospace equipment, aeronautical equipment, nuclear reactor control systems, life support equipment or systems, transportation machinery engine control or safety-related equipment.
This device is designed for use in household electric appliance, office automation equipment, audio and video equipment, computer communications equipment, test and measurement equipment, personal electronic equipment and transportation equipment (excluding engine control).
- The customer should select the proper thermal cutoff device, mounting location, and mounting method as appropriate for each application.
Verify whether the chosen selections are appropriate by repeatedly testing the final design for thermal cutoff under normal conditions as well as under predicted maximum abnormal conditions.
- Make designs so that the temperature of the body of the thermal cutoff does not exceed the temperatures shown in Table 1.
If, the temperature is exceeded on a regular basis, the thermal cutoff may start operating only at temperature lower than the normal operating temperature. Malfunctions may also occur. Even if the thermal cutoff's operating temperature is exceeded, it may malfunction.


Table 1.

Type Name	Body Temperature
SM065A0, SM065A1	45°C
SM072A0, SM072A1	52°C
SM095A0, SM095A1	75°C
SM110A0, SM110A1	90°C
SM126A0, SM126A1	106°C
SM129A0, SM129A1	106°C
SM130A0, SM130A1	110°C
SM134A0, SM134A1	114°C
SM145A0, SM145A1	125°C
SM164A0, SM164A1	140°C
SM182A0, SM182A1	140°C

- The body temperature of the thermal cutoff becomes higher as current passes through and might rise higher than the ambient operating temperature (see test data). The temperature may rise even higher depending on the mounting method and other conditions. Therefore, after mounting the thermal cutoff under the same conditions you would use for the actual application, work the final product and measure the body temperature of the thermal cutoff.
- Use the thermal cutoff with a voltage and current level lower than the rated level.
If the thermal cutoff is used with a voltage or current level higher than the rated level, the body of the thermal cutoff may be destroyed.
- Do not use the thermal cutoff in water, organic solvents or other liquids, or environments containing sulfurous acid gas, nitrous acid gas, or high humidity. Doing so will cause deterioration of the sealing resin, the thermal cutoff may operate, at lower than operating temperature, or any other malfunctions may occur. Also, the thermal cutoff may not operate even if its operating temperature is exceeded.


Lead wire process

- When bending the lead wire, in order to protect the resin seal from excessive pressure, secure the lead wire close to the case and bend the part beyond the secured section.



The lead wire should be bent at a distance 3 mm or more from the body of the fuse, and should not be twisted.

- The tensile strength applied to the lead wire should be 1kg or less for the SM type thermal cutoff.
- The strength applied to the body of the thermal cutoff should be 5 kg or less for the SM type thermal cutoff.




Mounting

SEFUSE can be mounted by soldering, caulking, or welding.

- If soldering, note that the thermal cutoff may not function because of excessive solder temperature. To prevent such malfunctions, for example, holding the lead near the case by a tool is effective for allowing the heat to escape, and the soldering should be done in short interval. Another effective method is to use a lower solder temperature and to solder at a location that is distant from the case.

- If caulking or welding, be careful to keep the resistance value of the connecting section low.
If the connecting section has a high resistance value, the passing current may generate an abnormally high temperature that will cause the thermal cutoff to operate (break the circuit).
- It is recommended that the connecting position should be 5 mm or more from the body of the thermal cutoff.



- After mounting the thermal cutoff, be careful not to apply force that may pull, push or twist the lead wires.

Storage

- The leads of SM164A and SM182A are silver-plated. Therefore, these parts may discolor because of sulfuration. In the case, the solder-ability of lead will decline. To avoid this, the SEFUSE should not keep around materials (such as cardboard or rubber, etc.) which generate sulfurous acid gas.

Recommendation

- Be careful when mounting the thermal cutoff because external force, heat, or a harmful atmosphere (containing excessive humidity or sulfurous acid gas) may damage the characteristics of the thermal cutoff. If applicable, it is recommended to warn general consumers who are not aware of the usage cautions for the thermal cutoff not to mount, remove or replace the thermal cutoff through a note to this effect in the user's manual and other related material.

If you desire any clarifications or explanations regarding these cautions, please call an NEC sales representative.

The values contained in this document were obtained under certain testing conditions at NEC. They are not guaranteed and are for reference only.

No part of this document may be copied or reproduced in any form or by any means without the prior written consent of NEC Corporation. NEC Corporation assumes no responsibility for any errors which may appear in this document.

NEC Corporation does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from use of a device described herein or any other liability arising from use of such device. No license, either express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC Corporation or others.

While NEC Corporation has been making continuous effort to enhance the reliability of its electronic components, the possibility of defects cannot be eliminated entirely. To minimize risks of damage or injury to persons or property arising from a defect in an NEC electronic component, customers must incorporate sufficient safety measures in its design, such as redundancy, fire-containment, and anti-failure features.

NEC devices are classified into the following three quality grades:

"Standard", "Special", and "Specific". The Specific quality grade applies only to devices developed based on a customer designated "quality assurance program" for a specific application. The recommended applications of a device depend on its quality grade, as indicated below. Customers must check the quality grade of each device before using it in a particular application.

Standard: Computers, office equipment, communications equipment, test and measurement equipment, audio and visual equipment, home electronic appliances, machine tools, personal electronic equipment and industrial robots

Special: Transportation equipment (automobiles, trains, ships, etc.), traffic control systems, anti-disaster systems, anti-crime systems, safety equipment and medical equipment (not specifically designed for life support)

Specific: Aircrafts, aerospace equipment, submersible repeaters, nuclear reactor control systems, life support systems or medical equipment for life support, etc.

The quality grade of NEC devices is "Standard" unless otherwise specified in NEC's Data Sheets or Data Books.

If customers intend to use NEC devices for applications other than those specified for Standard quality grade, they should contact an NEC sales representative in advance.

Anti-radioactive design is not implemented in this product.