

## BF\*X系列

型号	额定动作温度	实际动作温度	保持温度	极限温度	额定电压	额定电流	认证
Type No.	Rated Functioning Temperature $T_F$ (°C)	Fusing-off Temperature (°C)	Holding Temperature $T_H$ (°C)	Maximum Temp. Limit $T_M$ (°C)	Rated Voltage	Rated Current	VDE approval
BF-73X	73 °C	70 ± 2 °C	45 °C	150 °C	250V	16A	●
BF-84X	84 °C	82 ± 2 °C	58 °C	150 °C	250V	16A	●
BF-94X	94 °C	91 ± 3 °C	66 °C	150 °C	250V	16A	●
BF-99X	99 °C	96 ± 2 °C	71 °C	150 °C	250V	16A	●
BF-104X	104 °C	100 ± 2 °C	79 °C	150 °C	250V	16A	●
BF-113X	113 °C	109+3/-1 °C	84 °C	150 °C	250V	16A	●
BF-117X	117 °C	115 ± 2 °C	92 °C	160 °C	250V	16A	●
BF-121X	121 °C	119+2/-3 °C	94 °C	160 °C	250V	16A	●
BF-133X	133 °C	129 ± 2 °C	104 °C	160 °C	250V	16A	●
BF-142X	142 °C	139+2/-3 °C	114 °C	160 °C	250V	16A	●
BF-157X	157 °C	152 ± 2 °C	127 °C	172 °C	250V	16A	●
BF-172X	172 °C	169+3/-1 °C	144 °C	189 °C	250V	16A	●
BF-184X	184 °C	182+1/-3 °C	159 °C	210 °C	250V	16A	●
BF-192X	192 °C	188 ± 3 °C	164 °C	250 °C	250V	16A	●
BF-216X	216 °C	214+2/-3 °C	189 °C	380 °C	250V	16A	●
BF-229X	229 °C	226+3/-2 °C	190 °C	380 °C	250V	16A	●
BF-240X	240 °C	235 ± 3 °C	200 °C	300 °C	250V	16A	●