



- Features :
- Universal AC input / Full range
- 2 pole EURO plug
- Class II power (without earth pin)
- Protections: Short circuit / Over load / Over voltage
- No load power consumption <1.0W
- Pass LPS
- Fully enclosed plastic case
- TUV / CB / CE
- 1 year warranty




SPECIFICATION


ORDER NO.	GC15E-0P1J	GC15E-1P1J	GC15E-11P1J	GC15E-2P1J	GC15E-4P1J	
OUTPUT	SAFETY MODEL NO.	GPSU15E-0-CC	GPSU15E-1-CC	GPSU15E-1-1-CC	GPSU15E-2-CC	GPSU15E-4-CC
	DC VOLTAGE Note.2	3V	5.6V	7.2V	8.4V	14.4V
	RATED CURRENT	2.40A	2.14A	1.66A	1.78A	1.04A
	CURRENT RANGE	0 ~ 2.40A	0 ~ 2.14A	0 ~ 1.66A	0 ~ 1.78A	0 ~ 1.04A
	RATED POWER	7.2W	12W	12W	15W	15W
	RIPPLE & NOISE (max.) Note.3	50mVp-p	50mVp-p	80mVp-p	80mVp-p	120mVp-p
	VOLTAGE ADJ. RANGE	Fixed				
	VOLTAGE TOLERANCE Note.4	±5.0%	±5.0%	±5.0%	±3.0%	±3.0%
	LINE REGULATION Note.5	±1.0%	±0.5%	±0.5%	±0.5%	±0.5%
	LOAD REGULATION Note.6	±5.0%	±5.0%	±5.0%	±3.0%	±3.0%
SETUP, RISE, HOLD TIME	3000ms, 50ms, 16ms at full load					
INPUT	VOLTAGE RANGE	90 ~ 264VAC 135 ~ 370VDC				
	FREQUENCY RANGE	47 ~ 63Hz				
	EFFICIENCY (Typ.) Note.7	55%	65%	76%	78%	78%
	AC CURRENT	0.5A / 100VAC				
	INRUSH CURRENT (max.)	40A / 230VAC				
LEAKAGE CURRENT(max.)	0.25mA / 240VAC					
PROTECTION	OVER LOAD	115 ~ 250% rated output power Protection type : Constant current limiting, recovers automatically after fault condition is removed				
	OVER VOLTAGE	>120% rated output voltage Protection type : Clamp by zener diode				
ENVIRONMENT	WORKING TEMP.	0 ~ +50°C (Refer to output load derating curve)				
	WORKING HUMIDITY	20% ~ 90% RH non-condensing				
	STORAGE TEMP., HUMIDITY	-20 ~ +85°C, 10 ~ 95% RH				
	TEMP. COEFFICIENT	±0.03% / °C (0 ~ 50°C)				
SAFETY & EMC (Note. 8)	VIBRATION	10 ~ 500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes				
	SAFETY STANDARDS	UL60950-1, CSA22.2, EN60950-1 Approved				
	WITHSTAND VOLTAGE	I/P-O/P:3KVAC				
	ISOLATION RESISTANCE	I/P-O/P:100M Ohms / 500VDC				
	EMI CONDUCTION & RADIATION	Compliance to EN55022 class B				
OTHERS	HARMONIC CURRENT	Compliance to EN61000-3-2,3				
	EMS IMMUNITY	Compliance to EN61000-4-2,3,4,5,6,11, Light industry level, criteria A				
	MTBF	500Khrs min. MIL-HDBK-217F(25°C)				
CONNECTOR	DIMENSION	34*71*50mm (L*W*H)				
	PACKING	180g ; 60pcs / 12Kg / CARTON				
CONNECTOR	PLUG	Standard type P1J: 2.1φ * 5.5φ * 11mm, turning fork type center positive for stock ; Other type available by customer requested				
	CABLE	Standard type 18Awg UL1185 6ft and 5ft for 3V output only for stock ; Other type available by customer requested				
NOTE	<p>1.All parameters are specified at 230VAC input, rated load, 25°C 70% RH. Ambient.</p> <p>2.DC voltage: The output voltage set at point measure by plug terminal & 50% load.</p> <p>3.Ripple & noise are measured at 20MHz by using a 12" twisted pair terminated with a 0.1uf & 47uf capacitor.</p> <p>4.Tolerance: includes set up tolerance, line regulation, load regulation.</p> <p>5.Line regulation is measured from low line to high line at rated load.</p> <p>6.Load regulation is measured from 0% to 100% rated load</p> <p>7.Efficiency is measured at 230VAC.</p> <p>8.The power supply is considered a component which will be installed into a final equipment. The final equipment must be re-confirmed that it still meets EMC directives.</p>					

■ Mechanical Specification

Unit:mm



■ Charging Curve




■ Plug Assignment

Standard plug: P1J (option)

P1J	
P/N	OUTPUT
CENTER	+

■ Derating Curve



■ Static Characteristics

